



www.PegasusTech.net

# Pegasus AC6712

Android Handheld Terminal

## The Ultimate Android Mobile Computer Intelligence for every purpose

### Industries

Restaurant



Super Market



Warehouse



Logistics



Government



Book Store



Medication



Android



NFC



Wifi



Bluetooth



RFID



GPS



1D & 2D

### Features:

#### Industrial and Humanized Hardware Design

Industrial & humanized keypad design and tough 5.5 inch touch screen together with high resolution of 720\*1440 display shall match high standards in logistics, express and retail.

#### Octa-Core Processor & Large Memory

Android 10.0 OS with memory of 2GB RAM/16GB ROM or 4GB RAM/64GB ROM shall provide the highly standard experience.

#### Superior Data Communication and Security Guarantee

Double insurance of 4G & WIFI network and highly secured Android 10.0 system shall provide the high-speed data communication and perfect security guarantee.



www.PegasusTech.net

# Specification Sheet

## Industries

### Restaurant



### Super Market



### Warehouse



### Logistics



### Government



### Book Store



### Medication



Physical Characteristics		
Dimension	166mm(h)x79mm(w)x31mm(d)±2 mm	
Weight	Net weight : 600g (including battery & wrist strap)	
Display	Tough 5.5 in. TFT-LCD (720x1440) touch screen with backlight	
Backlight	Led backlight	
Expansions	1 PSAM, 1 SIM, 1 TF	
Battery	Rechargeable li-ion polymer, 3.8v, 9000mah	
Performance Characteristics		
CPU	Cortex a73 2.0ghz octa-core	
Operating system	Android 10.0	
Storage	2gb ram/16gb rom or 4gb ram/64gb rom, microsd (max 256gb expansion)	
User Environment		
Operating temp.	-20°C to 50°C	
Storage temp.	-20°C to 70°C	
Humidity	5%rh to 95%rh(non-condensing)	
Drop Specifications	5ft./1.5 m drop to concrete across the operating temperature range	
Sealing	Ip65, iec compliance	
ESD	±15kv air discharge, ±8kv direct discharge	
Development Environment		
SDK	Handheld-wireless software development kit	
Language	Java	
Environment	Android studio or eclipse	
Data Communication		
WWAN	Tdd-lte band 38, 39, 40, 41; fdd-lte band 1, 2, 3, 4, 5,7,8,12, 17, 20; Wcdma (850/1900/2100mhz); GSM/GPRS/edge (850/900/1800/1900mhz);	
WLAN	2.4ghz/5.0ghz dual frequency, ieee 802.11 a/b/g/n/ac	
WPAN	Bluetooth class v2.1+edr, Bluetooth v3.0+hs, Bluetooth v4.2	
GPS	GPS (embedded a-GPS), accuracy of 5 m	
Data Capture Barcode Reader (optional)		
2D Barcode	2D CMOS imager	Zebra se4710
	Symbologies	PDF417, micropdf417, composite, rss, tlc-39, Datamatrix, QR code, micro QR code, aztec, maxicode, postal codes, us postnet, us planet, uk postal, Australian postal, japan postal, Dutch postal. Etc...



www.PegasusTech.net

# Specification Sheet

## Industries

### Restaurant



### Super Market



### Warehouse



### Logistics



### Government



### Book Store



### Medication



Color Camera		
Resolution	Rear 13 megapixel, front 5.0 megapixel	
Lens	Auto-focus with LED flash	
RFID Reader (optional)		
RFID NFC	Frequency	13.56mhz
	Protocol	ISO 14443a&15693, nfc-ip1, nfc-ip2
	R/w range	2cm to 5cm
RFID UHF	Frequency	865~868mhz or 920~925mhz
	Protocol	EPC c1 gen2/ISO 18000-6c
	Antenna gain	Circular antenna(4dbi)
	R/w range	20 m (tags and environment dependent)
PSAM Security (optional)		
Protocol	ISO 7816	
Baudrate	9600, 19200, 38400,43000, 56000, 57600, 115200	
Slot	2 slots(maximum)	
Accessories		
Standard	1xpower supply; 1xlithium polymer battery; 1xtype-c cable	
Optional	Cradle	

