



www.PegasusTech.net

Mobile Printer PM300

Newly Design / 2-3 inch / Portable / Class-Leading

- Great looking design.
- Bluetooth 4.2 Low Energy and passive NFC tags for quick pair.
- Dual capabilities: Receipts & Labels
- Long-lasting battery and intelligent power consumption control for long work shifts.
- Compatible with multiple programming languages, reducing re-development.
- Visual editing apps, design at view, easy print.



Retailers



Transportation



Manufacturing



Traffic Enforcement

Specifications Sheet



Printer Specifications

Print Method:Direct Thermal
Resolution:203dpi/8dots/mm
Maximum Print Width:72mm
Maximum Print Speed:up to 120mm/s



Memory

RAM:8MB
FLASH:16MB



Font

Bitmap fonts : ASCII(8*16, 12*24, 16*32),
GBK(16*16,24*24, 32*32)BIG 5(16*16, 32*32)
TTF fonts can be download



Barcode symbologies

1D:Code 39, Code128JTF, EAN-8,
EAN-13 etc.
2D:QRCode, PDF417, DataMatrix, etc



Media Sensors

Gap, Blackmark,
Media out, Media cover open ,etc



Buttons & Display

Power button,
Feed/Configure button;
LED Display



Media Characteristics

Media width:42~80mm
Maximum Roll Outside Diameter:50mm
Media thickness:0.06~0.16mm
Media types:Direct Thermal



Battery

Li-Ion 7.4V 2500mAh



Communications

USB Type-C
Bluetooth 4.2 +2.1
2.4GHz&5GHz WIFI (optional)



Programming Languages

TSPC, CPCL, ESC/POS, etc.



Physical Characteristics

Dimension:118mm*105mm*62mm
Weight:450g



Environmental

Operating Temperature:0~50°C(32~122°F)
Storage Temperature:-20~60°C(-4~140°F)
Operating Humidity:
20%~85% non-condensing
Drop Spec:1.5m tested over operating
temp range