

A Reliable Operation & Performance Solution that fits your needs



Ethernet



USB

Features

- Direct Thermal Printing, No Ink or Cartridge required.
- 80mm thermal printer with Manual Paper cutter function, Interface: USB+LAN
- Low Cost and clear printing, print speed can reach to 160mm/s.
- Up to 60 Kms Head Life, Support Window software based on ESC/POS command.

Printing	
Printing Method	Thermal Line
Printing width	72mm
Resolution	576 Dots/Line Or 512 Dots/Line(8dots/mm,203dpi)
Printing Speed	160mm/s
Interface	USB+LAN+COM
Line Space	3.75mm(Can adjust line space by command)
Line No	Font A-32 Lines/Font B-42 Lines/Simple
Power	
Input	AC 110V/220V,50~60Hz
Output	DC 24V/2.5A
Cash Drawer output	DC 24V/1A
Physical characteristics	
Weight	1.15KG
Dimension	195*140*148(MM)
Environment	
Working: Temp	5 ~ 45°C, Humidity:10 ~ 80%
Storage: Temp	-10 ~ 50°C ,Humidity:10 ~ 90%(No dew)
Reliability Parameter	
Print Head Life	60-80KM(print density≤12.5)
Cutter Life	No Cutter
Software	
Driver	Linux,WinXP,Win7,Win8,Win8.1, Win 10



Paper Guard Plate



USB



Adaptor



80MM Paper