

Pegasus T312D 8 Inch LCD Non Touch Monitor



Panel	
Modal	L211B
Viewing Area	8.0 inches
Resolution	800 x 600
Active Display Area (mm)	111.3 x 84.7
Color	26.2k
Response Time TR/TF	10/15 ms
Contrast Ratio	500:1
Viewing Angle (Degree) Up/Down/Left/Right	50/ 70/ 70/ 70
Brightness	250 cd/m2 (LED Backlight)
Video Input	
VGA Signal	RGB Analog
Horizontal Frequency	31 to 48kHz
Vertical Frequency	56 to 72Hz
CVBS Signal	1.0Vp-p PAL/NTSC
Power Adaptor	
Input	Universal AC100~240V, 50/60Hz
Output	DC +5V
Power	
Management	VESA DPMS
Consumption	Less than 5W
Environment	
Storage Temp. (Degree C)	-25 to 70
Operating Temp. (Degree C)	0 to 42
Operating Humidity	10% to 85%
Rotation	
Vertical (Degree)	30°
Horizontal (Degree)	Anti-clockwise: 180, Clockwise: 30
Optional	
Glass	Strengthen Glass
Color	Light Gray / Black
Dummy Base Ports	PS/2, USB, RS232



Pegasus L211C 10 Inch Touch Panel Monitor



Panel	
Model	L211C
Viewing Area	10.1 inches
Resolution	1280 x 800
Active Display Area (mm)	216.96 (W) x 135.6(H)
Response Time (at 0 °C)	20 ms (ON), 20ms (OFF)
Contrast Ratio	500:1
LED Backlight Life	30,000 hours
Viewing Angle Up/Down/Left/Right	75°/ 70°/ 75°/ 75°
Luminance	200 cd/m ²
Environment	
Storage Temperature	-20 °C ~ 55 °C
Operating Temperature	0 °C ~ 50 °C
Operating Humidity	10% ~ 80%
Mounting	
Standard	VESA compliant (75mm x 75mm)
Optional	
Glass	Strengthen Glass
Touch Panel	ELO 5-wire resistive

Pegasus L211B 15 Inch POS Monitor With Zig-Zag Metal Stand



Panel	
Modal	T312D
Viewing Area	15 inches
Resolution	1024 x 768
Active Display Area (mm)	304.128(W) x 228.096(H)
Display Color	16,777,216 colors
Response Time	8 ms
Contrast Ratio	600:1
Viewing Angle	70° (Up) / 60° (Down) / 75° (Left) / 75° (Right)
Luminance	250 cd/m2
Video Input	
VGA Signal	RGB Analog
Power Adaptor	
Input	Universal AC100~240V, 50/60Hz
Output	DC +12V
Power	
Management	VESA DPMS
Consumption	less than 4W
Environment	
Storage Temperature	-25°C to 70°C
Operating Temperature	0°C to 42°C
Operating Humidity	10% ~ 85%
Rotation	
Vertical	30°
Mounting	
Standard	VESA Complaint (100mm x 100mm)
Optional	
Glass	Strengthen Glass
Touch panel	ELO 5-wire resistive
MSR	Programmable
Customer Display	2-line LCD display
	AP701A - 7" TFT Display
	AP801A - 8" TFT Display